



# TMS

## METAL DETECTOR MONOFREQUENCY SERIES "TMS"

### MAIN FEATURES BELT

- Structure and carpentry stainless steel.
- Brushless motors and drive boards.
- Adjustable belt speed from 10 to 50 m/min.

### MAIN FEATURES PROBES

- Sensitivity: adjustable by software from 0 to 100.
- Selectable programs: 256.
- Storable programs: 10.
- Alarm outputs: 2 with dry contacts, one of which immediate and one delayable from 0 to 10 min.
- Display: 80 alphanumeric characters (4 rows, 20 columns).
- Keyboard: 4 keys (F1, F2, +, -).
- Manual and software: in Italian.
- Digital management of sensing transducers.
- Software adjustment of response times.
- Synchronizes via photocell.
- High selectivity for the metal to be detected.
- Storage of the settings made about the product to be examined.
- Protection by two levels of password and key lock.
- Serial interface.
- Possibility of regular quality tests.



CODE	DIMENSIONS BELT SENZA ESPULSORE (mm)	DIMENSIONS BELT SENZA ESPULSORE (mm)	USEFUL HEIGHT (mm)
4249	150x820	150x1020	60
4250	150x870	150x1070	85
4254	150x920	150x1120	110
4256	150x970	150x1170	135
4258	150x1020	150x1220	160
4259	195x820	195x1070	60
4260	195x870	195x1120	85
4261	195x920	195x1170	110
4264	195x970	195x1220	135
4265	195x1020	195x1270	160
4266	240x820	240x1170	60
4267	240x870	240x1220	85
4268	240x920	240x1270	110
4270	240x970	240x1320	135
4271	240x1020	240x1370	160
4272	330x820	330x1270	60
4273	330x870	330x1320	85
4274	330x920	330x1370	110
4275	330x970	330x1420	135
4276	330x1020	330x1470	160
4277	510x820	510x1370	60
4278	510x870	510x1420	85
4279	510x920	510x1470	110
4280	510x970	510x1520	135
4281	510x1020	510x1570	160

#### Postadress:

TRÄDGÅRDSTEKNIK AB  
Helsingborgsvägen 578, Varalöv  
262 96 ÄNGELHOLM

Telefon : 0431-222 90  
Bg.nr : 5743-7980  
Org.nr : 556409-6120

#### URL:

[www.tradgardsteknik.se](http://www.tradgardsteknik.se)  
E-postadress:  
[info@tradgardsteknik.se](mailto:info@tradgardsteknik.se)